



SULFANITE®

SOUR GAS RESISTANCE UP TO 40% H₂S

SULFANITE®

10% H₂S –MODIFIED HNBR ELASTOMER RANGE

-20°C to 100°C (-4°F to 212°F)

The Rubberatkins **SULFANITE®** material range was developed for applications requiring H₂S and acid resistance. **SULFANITE®** materials will handle H₂S exposure up to and including 10%.

SULFANITE® ULTRA

40% H₂S –MODIFIED FKM ELASTOMER RANGE

-20°C to 177°C (-4°F to 350°F)

The **SULFANITE ULTRA®** takes you from 10% all the way up to 40% resistance.

The **SULFANITE®** material range has been subject to ISO, API and NORSOK testing to confirm the material integrity and its resistance to sour gas. **SULFANITE®** materials have been developed to meet aggressive environmental conditions as well as consideration of the various product types and applications the materials will be subjected to.

SULFANITE® LT

LOW TEMPERATURE RANGE

-30°C to 177°C (-22°F to 350°F)

Rubberatkins has also developed a low-temperature range of **SULFANITE®** materials for specific applications, with testing available to your chosen international standards.

INTERNATIONAL TESTING STANDARDS:

NORSOK M710 –RGD & H₂S

ISO 23936-2

NACE TM0187

NACE TM0296

API 6A (ISO 10423)



FEATURES

- Independently verified Lab and field-tested
- A full range of material suitable for environments and temperatures
- A full range of material for different applications and product lines

BENEFITS

- Assured sealing integrity through certification and qualification
- Materials specifically designed for each application, offering better performance
- Increased longevity of life-span and performance that reduces NPT

PRODUCTS

- Cups
- Packing Elements
- Seal Stacks
- O-rings
- Gland Seals
- Custom Parts